

Description

Fastener Length: 45/64", Thread: 1/4-28, Head Width: 7/32", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS144DH11
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-206-0821
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS144DH11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	0.673 Inches Minimum And 0.703 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.430 Inches Minimum And 0.438 Inches Maximum
Head Height:	0.226 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Special Features:	6 Drilled Holes
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas144dh11 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS144DH11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.