

**Description**

Fastener Length: 3/4", Hole Diameter: ", Thread: 1/4-18, Head Width: 7/32", Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS144DH12
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-282-4745
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS144DH12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Fastener Length:</b>	0.735 Inches Minimum And 0.765 Inches Maximum
<b>Head Diameter:</b>	0.430 Inches Minimum And 0.438 Inches Maximum
<b>Head Height:</b>	0.226 Inches Nominal
<b>Hole Diameter:</b>	0.055 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Width Across Flats:</b>	0.219 Inches Minimum And 0.221 Inches Maximum
<b>Hole Quantity:</b>	6
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Round
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or An-qq-s-690 Cond. E4 Fed Spec 4th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS144DH12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.