

Description

Fastener Length: 3/4", Hole Diameter: ", Thread: 1/4-18, Head Width: 7/32", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS144DH12 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-282-4745 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS144DH12 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Fastener Length: | 0.735 Inches Minimum And 0.765 Inches Maximum |
| Head Diameter: | 0.430 Inches Minimum And 0.438 Inches Maximum |
| Head Height: | 0.226 Inches Nominal |
| Hole Diameter: | 0.055 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.219 Inches Minimum And 0.221 Inches Maximum |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Round |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or An-qq-s-690 Cond. E4 Fed Spec 4th Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS144DH12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.