

Description

Fastener Length: 61/64", Thread: 1/4-28, Head Width: 7/32", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS144DH15 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-807-9281 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS144DH15 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.500 Inches Nominal |
| Fastener Length: | 0.923 Inches Minimum And 0.953 Inches Maximum |
| Head Style: | Bevel-conical |
| Head Diameter: | 0.923 Inches Minimum And 0.953 Inches Maximum |
| Head Height: | 0.226 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.219 Inches Minimum And 0.221 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unc |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS144DH15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.