

**Description**

Fastener Length: 53/64", Hole Diameter: ", Thread: 1/4-24, Head Width: 5/16", Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS145DH13
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-208-1015
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS145DH13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.5475 Inches Minimum And 0.5775 Inches Maximum
<b>Fastener Length:</b>	0.7875 Inches Minimum And 0.8275 Inches Maximum
<b>Head Style:</b>	Bevel-conical
<b>Head Diameter:</b>	0.523 Inches Minimum And 0.531 Inches Maximum
<b>Head Height:</b>	0.276 Inches Nominal
<b>Hole Diameter:</b>	0.055 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Width Across Flats:</b>	0.313 Inches Minimum And 0.315 Inches Maximum
<b>Hole Quantity:</b>	6
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Round
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 6150 Overall Or Steel Comp 8740 Overall Or Steel Comp 3140 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Condition C,4 Mil Spec 1st Material Response Overall Or Mil-s-6049 Condition C,4 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Condition C,4 Mil Spec 3rd Material Response Overall Or Qq-s-690 Condition E,4 Fed Spec 4th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS145DH13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.