

Description

Fastener Length: 53/64", Hole Diameter: ", Thread: 1/4-24, Head Width: 5/16", Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS145DH13
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-208-1015
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS145DH13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.5475 Inches Minimum And 0.5775 Inches Maximum
Fastener Length:	0.7875 Inches Minimum And 0.8275 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.523 Inches Minimum And 0.531 Inches Maximum
Head Height:	0.276 Inches Nominal
Hole Diameter:	0.055 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Round
Material:	Steel Comp 4140 Overall Or Steel Comp 6150 Overall Or Steel Comp 8740 Overall Or Steel Comp 3140 Overall
Material Document And Classification:	Mil-s-5000 Condition C,4 Mil Spec 1st Material Response Overall Or Mil-s-6049 Condition C,4 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Condition C,4 Mil Spec 3rd Material Response Overall Or Qq-s-690 Condition E,4 Fed Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS145DH13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.