



Military-Fasteners.com

P/N NAS1466-02A

Description

NAS1466-02A

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS146602A |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5320-01-056-0199 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1466-02A Specifications

| | |
|---|---|
| Head Style: | Err-090 |
| Head Height: | 0.099 Inches Minimum And 0.111 Inches Maximum |
| Shank Diameter: | 0.2010 Inches Minimum And 0.2025 Inches Maximum |
| Head Major Diameter: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.095 Inches Minimum And 0.156 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Astm A547 Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1466 Professional/industrial Association Standard |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/NAS1466-02A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.