



★ FASTENERS

Military-Fasteners.com

P/N NAS1466-05

## Description

nom. size: 0.19", grip: 0.312", cadmium plated steel, protruding head, pull type

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS146605
Minimum Qty (MOQ):	25
NSN:	5320-00-680-3598
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1466-05 Specifications

<b>Fastener Length:</b>	1.810 Inches Minimum And 2.010 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.099 Inches Minimum And 0.111 Inches Maximum
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.297 Inches Minimum And 0.327 Inches Maximum
<b>Grip Length:</b>	0.282 Inches Minimum And 0.344 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/NAS1466-05](https://military-fasteners.com/pins/pin_rivets/NAS1466-05) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.