

Description

cadmium plated steel protruding head pull type (huck bolt), nom. size: 0.190, grip: 0.375

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS146606
Minimum Qty (MOQ):	10
NSN:	5320-00-619-0157
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1466-06 Specifications

Fastener Length:	1.940 Inches Minimum And 2.140 Inches Maximum
Head Style:	Err-090
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-riquet, Multiple Grooved
Head Major Diameter:	0.297 Inches Minimum And 0.327 Inches Maximum
Grip Length:	0.345 Inches Minimum And 0.406 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1466-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.