

Description

cadmium plated steel protruding head pull type (huck bolt), nom. size: 0.190, grip: 0.375

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS146606 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-619-0157 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS1466-06 Specifications

| | |
|---|---|
| Fastener Length: | 1.940 Inches Minimum And 2.140 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.099 Inches Minimum And 0.111 Inches Maximum |
| Shank Diameter: | 0.188 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Grip Length: | 0.345 Inches Minimum And 0.406 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1466-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.