

## Description

cadmium plated steel protruding head pull type (huck bolt), nom. size: 0.190, grip: 0.562

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS146609
Minimum Qty (MOQ):	10
NSN:	5320-00-680-4456
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1466-09 Specifications

<b>Fastener Length:</b>	2.310 Inches Minimum And 2.510 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.099 Inches Minimum And 0.111 Inches Maximum
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.297 Inches Minimum And 0.327 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.532 Inches Minimum And 0.594 Inches Maximum
<b>Features Provided:</b>	Casehardened
<b>Hardness Rating:</b>	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
<b>Specification/standard Data:</b>	80205-nas1466 Professional/industrial Association Standard

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/NAS1466-09](https://military-fasteners.com/rivets/pin_rivets/NAS1466-09) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.