

Description

cadmium plated steel protruding head pull type (huck bolt), nom. size: 0.190, grip: 0.688

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS146611
Minimum Qty (MOQ):	10
NSN:	5320-00-702-8513
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1466-11 Specifications

Fastener Length:	2.560 Inches Minimum And 2.760 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.297 Inches Minimum And 0.327 Inches Maximum
Grip Length:	0.657 Inches Minimum And 0.719 Inches Maximum
Features Provided:	Casehardened
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	37.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Qq-w-405 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1466 Professional/industrial Association Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1466-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.