

Description

Fastener Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS146614A
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-206-3502
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1466-14A Specifications

Fastener Length:	1.098 Inches Minimum And 1.118 Inches Maximum
Head Style:	Err-090
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.2010 Inches Minimum And 0.2025 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.297 Inches Minimum And 0.327 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.845 Inches Minimum And 0.906 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1466 Professional/industrial Association Standard

How to Order

Order this swage pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1466-14A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.