

Description

Swage Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS14663A |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-00-701-0332 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1466-3A Specifications

| | |
|---|---|
| Head Style: | Straight Pan |
| Head Height: | 0.099 Inches Minimum And 0.111 Inches Maximum |
| Shank Diameter: | 0.2010 Inches Minimum And 0.2025 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.157 Inches Minimum And 0.219 Inches Maximum |
| Features Provided: | Casehardened |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Steel Comp 8740 Overall Or Steel Comp 430 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Astm A547 Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 C3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1446 Professional/industrial Association Standard |

How to Order

Order this swage pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1466-3A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.