

Description

Swage Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS14663A
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-701-0332
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1466-3A Specifications

Head Style:	Straight Pan
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.2010 Inches Minimum And 0.2025 Inches Maximum
Shank Style:	Pin-riquet, Multiple Grooved
Head Major Diameter:	0.297 Inches Minimum And 0.327 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.157 Inches Minimum And 0.219 Inches Maximum
Features Provided:	Casehardened
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall Or Steel Comp 430 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Astm A547 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 C3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1446 Professional/industrial Association Standard

How to Order

Order this swage pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1466-3A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.