

Description

Swage Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1466H16 |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5320-01-307-7924 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1466H16 Specifications

| | |
|-------------------------------------|--|
| Head Style: | Err-090 |
| Head Height: | 0.099 Inches Minimum And 0.111 Inches Maximum |
| Shank Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Grip Length: | 0.970 Inches Minimum And 1.031 Inches Maximum |
| Features Provided: | Casehardened And Sealant Vent Groove |
| Material: | Steel Comp 8740 Overall Or Steel Comp 4340 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Specification/standard Data: | 80205-nas1466 Professional/industrial Association Standard |

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1466H16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.