

**Description**

Fastener Length: 1-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1466N05
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-003-8026
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N NAS1466N05 Specifications

<b>Fastener Length:</b>	1.810 Inches Minimum And 2.010 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.099 Inches Minimum And 0.111 Inches Maximum
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.297 Inches Minimum And 0.327 Inches Maximum
<b>Grip Length:</b>	0.282 Inches Minimum And 0.344 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	76.1 Rockwell Superficial 15-n Minimum Overall And 80.9 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	2620 Single Pounds Per Square Inch
<b>Special Features:</b>	Double Shear Strength 5240 Psi
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Qq-w-405 Fed Spec All Material Responses Overall
<b>Surface Treatment:</b>	Nickel Overall Or Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std All Treatment Responses Overall
<b>Specification/standard Data:</b>	80205-nas1466 Professional/industrial Association Standard

## How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1466N05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.