

Description

Fastener Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1466N05
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-003-8026
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1466N05 Specifications

Fastener Length:	1.810 Inches Minimum And 2.010 Inches Maximum
Head Style:	Err-090
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.1880 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.297 Inches Minimum And 0.327 Inches Maximum
Grip Length:	0.282 Inches Minimum And 0.344 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	76.1 Rockwell Superficial 15-n Minimum Overall And 80.9 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	2620 Single Pounds Per Square Inch
Special Features:	Double Shear Strength 5240 Psi
Material:	Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Qq-w-405 Fed Spec All Material Responses Overall
Surface Treatment:	Nickel Overall Or Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std All Treatment Responses Overall
Specification/standard Data:	80205-nas1466 Professional/industrial Association Standard

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1466N05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.