

**Description**

Swage Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1466N10
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-499-3766
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1466N10 Specifications

<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.099 Inches Minimum And 0.111 Inches Maximum
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1885 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.297 Inches Minimum And 0.327 Inches Maximum
<b>Grip Length:</b>	0.595 Inches Minimum And 0.656 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Nickel Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1466 Professional/Industrial Association Standard

## How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1466N10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.