

Description

Swage Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1466N14
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-172-2619
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1466N14 Specifications

Head Style:	Err-090
Head Height:	0.099 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.1880 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-riquet, Multiple Grooved
Head Major Diameter:	0.297 Inches Minimum And 0.327 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.845 Inches Minimum And 0.906 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Aisi Assn Std 1st Material Response Overall Or Aisi Assn Std 2nd Material Response Overall Or Astm A547 Assn Std 3rd Material Response Overall
Surface Treatment:	Nickel Overall And Chromate Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1466 Professional/Industrial Association Standard

How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1466N14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.