

**Description**

Swage Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1466N14
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-172-2619
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1466N14 Specifications

<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.099 Inches Minimum And 0.111 Inches Maximum
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Pin-riquet, Multiple Grooved
<b>Head Major Diameter:</b>	0.297 Inches Minimum And 0.327 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.845 Inches Minimum And 0.906 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std 1st Material Response Overall Or Aisi Assn Std 2nd Material Response Overall Or Astm A547 Assn Std 3rd Material Response Overall
<b>Surface Treatment:</b>	Nickel Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1466 Professional/Industrial Association Standard

## How to Order

Order this swage pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1466N14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.