

## Description

Swage Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS146808A
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-229-8198
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1468-08A Specifications

<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.128 Inches Minimum And 0.147 Inches Maximum
<b>Shank Diameter:</b>	0.2635 Inches Minimum And 0.2650 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.390 Inches Minimum And 0.430 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.470 Inches Minimum And 0.531 Inches Maximum
<b>Features Provided:</b>	Casehardened
<b>Minimum Tensile Strength:</b>	1600000 Pounds Per Square Inch
<b>Hardness Rating:</b>	77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1468 Professional/industrial Association Standard

## How to Order

Order this swage pin from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/NAS1468-08A](https://military-fasteners.com/rivets/pin_rivets/NAS1468-08A) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.