

Description

Fastener Length: 3"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS146810 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-531-0736 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1468-10 Specifications

| | |
|---|---|
| Fastener Length: | 2.880 Inches Minimum And 3.080 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.128 Inches Minimum And 0.147 Inches Maximum |
| Shank Diameter: | 0.248 Inches Minimum And 0.250 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.390 Inches Minimum And 0.430 Inches Maximum |
| Grip Length: | 0.595 Inches Minimum And 0.656 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this swage pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1468-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.