

## Description

Swage Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS146810A                                  |
| Minimum Qty (MOQ):      | 10 EA                                       |
| NSN:                    | 5320-01-232-7477                            |
| Schedule B:             | 7318.24.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N NAS1468-10A Specifications

|   |   |
|---|---|
| <b>Head Style:</b>                                    | Err-090   |
| <b>Head Height:</b>                                   | 0.128 Inches Minimum And 0.147 Inches Maximum   |
| <b>Shank Diameter:</b>                                | 0.2480 Inches Minimum And 0.2495 Inches Maximum   |
| <b>Shank Style:</b>                                   | Pin-rivet, Multiple Grooved   |
| <b>Head Major Diameter:</b>                           | 0.390 Inches Minimum And 0.430 Inches Maximum   |
| <b>Lubrication:</b>                                   | Cetyl Alcohol   |
| <b>Grip Length:</b>                                   | 0.595 Inches Minimum And 0.656 Inches Maximum   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 77.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall                     |
| <b>Material Document And Classification:</b>          | Astm A547 Assn Std All Material Responses Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall                                     |
| <b>Specification/standard Data:</b>                   | 80205-nas1468 Professional/industrial Association Standard  |

## How to Order

Order this swage pin from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/NAS1468-10A](https://military-fasteners.com/rivets/pin_rivets/NAS1468-10A) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.