

## Description

Fastener Length: 3-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS146811A
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-214-1417
Schedule B:	7318.24.0000
ECCN:	EAR99



## P/N NAS1468-11A Specifications

<b>Fastener Length:</b>	3.000 Inches Minimum And 3.200 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.128 Inches Minimum And 0.147 Inches Maximum
<b>Shank Diameter:</b>	0.2635 Inches Minimum And 0.2650 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.390 Inches Minimum And 0.430 Inches Maximum
<b>Grip Length:</b>	0.657 Inches Minimum And 0.719 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1468 Professional/industrial Association Standard

## How to Order

Order this swage pin from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/NAS1468-11A](https://military-fasteners.com/rivets/pin_rivets/NAS1468-11A) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.