

**Description**

Fastener Length: 3-3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS146822                                   |
| Minimum Qty (MOQ):      | 1 EA  |
| NSN:                    | 5320-00-616-4769                            |
| Schedule B:             | 7318.24.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1468-22 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 3.250 Inches Minimum And 3.450 Inches Maximum                       |
| <b>Head Style:</b>                                    | Err-090   |
| <b>Head Height:</b>                                   | 0.128 Inches Minimum And 0.147 Inches Maximum                       |
| <b>Shank Diameter:</b>                                | 0.248 Inches Minimum And 0.249 Inches Maximum                       |
| <b>Shank Style:</b>                                   | Pin-rivet, Multiple Grooved   |
| <b>Head Major Diameter:</b>                           | 0.390 Inches Minimum And 0.430 Inches Maximum                       |
| <b>Grip Length:</b>                                   | 1.375 Inches Minimum And 1.385 Inches Maximum                       |
| <b>Hardness Rating:</b>                               | 37.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall |
| <b>Material:</b>                                      | Steel Comp 4037 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-8695 Cond C4 Mil Spec Single Material Response Overall        |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall       |
| <b>Specification/standard Data:</b>                   | 80205-nas1468 Professional/Industrial Association Standard          |

## How to Order

Order this swage pin from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/NAS1468-22](https://military-fasteners.com/rivets/pin_rivets/NAS1468-22) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.