

Description

Fastener Length: 3-3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS146822
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-616-4769
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1468-22 Specifications

<b>Fastener Length:</b>	3.250 Inches Minimum And 3.450 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.128 Inches Minimum And 0.147 Inches Maximum
<b>Shank Diameter:</b>	0.248 Inches Minimum And 0.249 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.390 Inches Minimum And 0.430 Inches Maximum
<b>Grip Length:</b>	1.375 Inches Minimum And 1.385 Inches Maximum
<b>Hardness Rating:</b>	37.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-s-8695 Cond C4 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1468 Professional/industrial Association Standard

## How to Order

Order this swage pin from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/NAS1468-22](https://military-fasteners.com/rivets/pin_rivets/NAS1468-22) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.