

Description

Fastener Length: 3-37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS146828
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-702-2897
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1468-28 Specifications

Fastener Length:	3.380 Inches Minimum And 3.580 Inches Maximum
Head Style:	Err-090
Head Height:	0.128 Inches Minimum And 0.147 Inches Maximum
Shank Diameter:	0.248 Inches Minimum And 0.250 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.390 Inches Minimum And 0.430 Inches Maximum
Grip Length:	1.720 Inches Minimum And 1.781 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1468 Professional/industrial Association Standard

How to Order

Order this swage pin from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/NAS1468-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.