

## P/N NAS1468H07

### **Description**

Swage Pin part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

| SKU / Model:       | NAS1468H07       |
|--------------------|------------------|
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5320-01-307-7922 |
| Schedule B:        | 7318.24.0000     |
| ECCN:              | 9A991            |



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1468H07 Specifications

| Head Style:                  | Err-090  |
|------------------------------|--|
| Head Height:                 | 0.128 Inches Minimum And 0.147 Inches Maximum              |
| Shank Diameter:              | 0.248 Inches Minimum And 0.249 Inches Maximum              |
| Shank Style:                 | Pin-rivet, Multiple Grooved                                |
| Head Major Diameter:         | 0.390 Inches Minimum And 0.430 Inches Maximum              |
| Grip Length:                 | 0.407 Inches Minimum And 0.469 Inches Maximum              |
| Features Provided:           | Casehardened And Sealant Vent Groove                       |
| Minimum Tensile Strength:    | 160000 Pounds Per Square Inch                              |
| Material:                    | Steel Comp 8740 Overall Or Steel Comp 4340 Overall         |
| Surface Treatment:           | Cadmium Overall And Chromate Overall                       |
| Specification/standard Data: | 80205-nas1468 Professional/industrial Association Standard |

## **How to Order**

Order this swage pin from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1468H07">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1468H07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.