

Description

Fastener Length: 13/16", Hole Diameter: 1/16", Thread: 3/8-24, Head Width: 3/8", Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS146DH13
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-638-3188
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS146DH13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.662 Inches Minimum And 0.712 Inches Maximum
Fastener Length:	0.797 Inches Minimum And 0.827 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.615 Inches Minimum And 0.625 Inches Maximum
Head Height:	0.333 Inches Minimum And 0.353 Inches Maximum
Hole Diameter:	0.073 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.376 Inches Minimum And 0.379 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Round
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3135 Overall Or Steel Comp 3140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas148 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS146DH13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.