

**Description**

Fastener Length: 13/16", Hole Diameter: 1/16", Thread: 3/8-24, Head Width: 3/8", Thread Length: 45/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS146DH13                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-638-3188                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS146DH13 Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Thread Class:</b>                | 3a  |
| <b>Thread Direction:</b>            | Right-hand  |
| <b>Thread Length:</b>               | 0.662 Inches Minimum And 0.712 Inches Maximum   |
| <b>Fastener Length:</b>             | 0.797 Inches Minimum And 0.827 Inches Maximum   |
| <b>Head Style:</b>                  | Bevel-conical   |
| <b>Head Diameter:</b>               | 0.615 Inches Minimum And 0.625 Inches Maximum   |
| <b>Head Height:</b>                 | 0.333 Inches Minimum And 0.353 Inches Maximum   |
| <b>Hole Diameter:</b>               | 0.073 Inches Nominal  |
| <b>Internal Drive Style:</b>        | Hexagon   |
| <b>Nominal Thread Diameter:</b>     | 0.375 Inches  |
| <b>Width Across Flats:</b>          | 0.376 Inches Minimum And 0.379 Inches Maximum   |
| <b>Hole Quantity:</b>               | 6   |
| <b>Hole Type:</b>                   | Drilled   |
| <b>Thread Quantity Per Inch:</b>    | 24  |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch   |
| <b>Hole Configuration Style:</b>    | Round   |
| <b>Material:</b>                    | Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3135 Overall Or Steel Comp 3140 Overall |
| <b>Surface Treatment:</b>           | Cadmium Overall And Chromate Overall  |
| <b>Thread Series Designator:</b>    | Unjf  |
| <b>Specification/standard Data:</b> | 80205-nas148 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS146DH13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.