

P/N NAS1473A08

Description

Thread: 8-32, self-locking capped nutplate, floating two lug, steel nut and shell, crimp lock, temperature range is between -65F and 225F, dry lubricant film coating, NAS1473 series nutplate

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

F1968-08

SKU / Model: NAS1473A08

Minimum Qty (MOQ): 10

NSN: 5310-00-849-7028

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1473A08 Specifications

Three d Class	
Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Overall Height:	0.640 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.989 Inches Maximum
Nut Height:	0.313 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.568 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes	0.686 Inches Minimum And 0.690 Inches Maximum
Along Length:	0.000 menes Minimum And 0.090 menes Maximum
Temp Rating:	-65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	60.0 Shore Durometer A Nominal
Nominal Thread Size:	0.164 Inches
Material:	Rubber Synthetic Seal
Material:	Steel Nut
Material:	Steel Shell
Material:	Steel Washer Or Aluminum Alloy Washer
Material Document And Classification:	Mil-r-6855 Class 1 Grade 60 Mil Spec Single Material Response Seal
Surface Treatment Document And Classification:	Mil-a-8625 Type 1 Mil Spec 1st Treatment Response Washer Or Mil-c-5541 Mil Spec 2nd Treatment Response Washer Or Qq-p-416 Fed Spec 3rd Treatment Response Washer
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-416 Type2,class3 Fed Spec Single Treatment Response Shell

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1473A08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1473A08 and selecting the