

**P/N NAS1473A4** 

Military-Fasteners.com

#### Description

thread: 1/4-28, self-locking, capped, two lug steel nut and shell

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1473A4
Minimum Qty (MOQ):	10
NSN:	5310-00-990-3591
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1473A4 Specifications

Thread Direction:Right-handLocking Feature:Peaviling Torque All Metal DesignCounterbore Diameter:0.298 Inches MaximumMounting Hole Diameter:0.755 Inches MaximumNot Height:0.998 Inches Minimum And 0.103 Inches MaximumNut Longth:0.298 Inches MaximumNut Length:0.372 Inches MaximumNut Height:0.372 Inches MaximumPiate0.303 Inches MaximumPiate Nut Longth:0.353 Inches MaximumNut Height:0.353 Inches MaximumNut Hought:0.353 Inches MaximumNut Gourterbore Depth:0.658 Inches MaximumNut Gourterbore Depth:0.658 Inches MaximumNut Gourterbore Depth:0.658 Inches MaximumStance From Aperture Contermonter9.158 Inches Minimum NutDistance From Aperture Contermonterbore0.981 Inches Minimum And 0.505 Inches MaximumCenter0.991 Inches Minimum And 0.505 Inches MaximumCenter0.991 Inches Minimum And 0.020 Inches MaximumCenter Distance Between Mounting0.991 Inches MaximumThread Series:0.991 Inches Minimum And 0.020 Inches MaximumThread Series:0.991 Inches Minimum And 0.020 Inches MaximumThread Series:0.991 Inches MaximumNumani Thread Series:0.991 Inches MaximumNoming Thread Series:0.991 Inches MaximumNumani Thread Series:0.991 Inches MaximumNumani Thread Series:0.991 Inches MaximumNumani Thread Series:0.991 Inches MaximumMaterial:0.801 Inches MaximumMateria	Thread Class:	3b
Locking Feature:Pevaling Torque All Metal DesignCounterbore Diameter:0.259 Inches Minimum NutOverall Height:0.755 Inches MaximumMunting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:1.296 Inches MaximumNut Height:0.372 Inches MaximumNut Height:0.372 Inches MaximumPlate Thickness:0.303 Inches MaximumPlate Thickness:0.303 Inches MaximumNut Guight:0.458 Inches Minimu NutNut Guight:0.459 Inches MaximumNut Guight:0.459 Inches MaximumNut Guight:0.459 Inches Minimum And 0.505 Inches MaximumFeature:0.99 Inches Minimum And 0.505 Inches MaximumFeature:0.99 Inches Minimum And 0.505 Inches MaximumFeature:0.99 Inches Minimum And 0.505 Inches MaximumFeature:0.50 Inches MaximumFeature:0.50 Inches MaximumThread Scies:0.50 Inches MaximumFeature:0.50 Inches MaximumThread Scies:0.50 Inches MaximumFeature:0.50 Inches MaximumThread Scies:0.50 Inches MaximumThread Scies:0.50 Inches MaximumMaterial:0.50 Inches MaximumMaterial:0.50 Inches MaximumMaterial:0.5		
Counter/ore Diameter:0.289 Inches Maximum NutOverall Height:0.755 Inches Maximum And 0.103 Inches MaximumMounting Hole Diameter:0.909 Inches Maximum And 0.103 Inches MaximumNut Style:PateNut Length:0.296 Inches MaximumNut Length:0.372 Inches MaximumNut Height:0.300 Inches MaximumPlate Hickness:0.300 Inches MaximumNut Good Inches Maximum0.300 Inches MaximumNut Guotter/ore Depth:0.315 Inches MaximumNut Guotter/ore Depth:0.315 Inches Maximum AutNut Guotter/ore Depth:0.315 Inches Maximum AutNut Guotter/ore Depth:0.496 Inches MaximumDiatance From Aperture Center To Mounting Ho240 Inches MaximumObtance From Aperture Center To Mounting Ho0.999 Inches MaximumBeat Statisches Edited0.990 Inches MaximumCenter:0.990 Inches Maximum And 0.505 Inches MaximumTered Series:0.990 Inches Maximum And 0.505 Inches MaximumThread Series:0.990 Inches Maximum And 0.020 Inches MaximumThread Series:0.990 Inches Maximum And 0.020 Inches MaximumThread Series:0.500 Inches Maximum And 0.020 Inches MaximumThread Series:0.500 Inches Maximum And 0.020 Inches MaximumThread Series:0.500 InchesMaterial:0.500 InchesMaterial:0.500 InchesMaterial:0.500 InchesMaterial:0.500 InchesMaterial:0.500 InchesMaterial:0.500 InchesMaterial:0.500 Inches		
Overall Height:0.755 Inches MaximumMounting Hole Diameter:0.98 Inches Maximum And 0.103 Inches MaximumNut Holp Ciameter:0.98 Inches MaximumNut Length:1.296 Inches MaximumNut Height:0.372 Inches MaximumPlate Thickness:0.303 Inches MaximumPlate Thickness:0.303 Inches MaximumNut Gunterbore Depth:0.668 Inches MaximumNut Mounting Provision:Taright HolesNut Mounting Provision:Taright HolesPlates Ciencer Distance Retween Mounting Moles Animum And 0.505 Inches MaximumCenter Coeffer Distance Retween Mounting Moles Animum And 0.505 Inches MaximumCenter Coeffer Distance Retween Mounting Moles Animum And 0.505 Inches MaximumThread Series:0.969 Inches Minimum And 0.505 Inches MaximumTempe Ating:0.500 Engensteriation:Thread Series:0.969 Inches Minimum And 0.505 Inches MaximumTempe Ating:0.500 Engensteriation:Thread Series:0.969 Inches Minimum And 0.505 Inches MaximumTempe Ating:0.500 Engensteriation:Thread Series:0.960 Engensteriation:Thread Series:0.960 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:Material:0.500 Engensteriation:<	Counterbore Diameter:	
Nontrigr Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Height:IA26 Inches MaximumNut Height:0.302 Inches MaximumPlate Thickness:0.303 Inches MaximumPlate Mickness:0.668 Inches MaximumNut Height:0.668 Inches MaximumNut Holght:0.668 Inches MaximumNut Holght:0.658 Inches Minimum NutNut Mounting Provision:0.135 Inches Minimum NutMounting Hole Arrangement Style:1.016Plates:0.909 Inches Minimum And 0.505 Inches MaximumCenter:0.999 Inches Minimum And 0.505 Inches MaximumThread Series:0.999 Inches Minimum And 0.505 Inches MaximumMaterial:0.505 Inches MaximumMaterial:0.505	Overall Height:	
Nut StylePietNut Length:1.296 Inches MaximumNut Height:0.370 Inches MaximumPiate Thickness:0.300 Inches MaximumPiate Thickness:0.668 Inches MaximumNut Gounterbore Depth:0.668 Inches Maximum NutNut Mounting Provision:0.135 Inches Maximum NutNut Mounting Provision:0.496 Inches MaximumDistance From Aperture Center Doff0.496 Inches MaximumCenter:0.495 Inches Minimum And 0.505 Inches MaximumCenter:0.998 Inches Minimum And 0.505 Inches MaximumCenter:0.998 Inches Minimum And 1.002 Inches MaximumTema Rating:0.998 Inches Minimum And 1.002 Inches MaximumCenter:0.998 Inches Minimum And 1.002 Inches MaximumTema Rating:0.998 Inches MaximumTema Quantity Per Inch:0.908 Inches MaximumMateria:0.908 Inches M	-	0.098 Inches Minimum And 0.103 Inches Maximum
Nu Length:1.296 Inches MaximumNut Height:0.372 Inches MaximumPlate Mich0.308 Inches MaximumPlate Width:0.668 Inches Maximum NutNut Courterbore Depth:0.135 Inches Minimum NutNut Mounting Provision:5 Kaight HolesNut Mounting Provision:0.408 Inches Minimum Aut 0.505 Inches MaximumDistage From Aperture Center Distance Between Mounting0.998 Inches Minimum Aut 0.505 Inches MaximumCenter:0.998 Inches Minimum Aut 0.505 Inches MaximumTemp Rating:0.998 Inches Minimum Aut 0.505 Inches MaximumTemp Rating:0.508 Inches Minimum Aut 0.505 Inches MaximumMaterial:0.608 Inches Minimum Aut 0.505 Inches MaximumMaterial: <td< th=""><th>-</th><th>Plate</th></td<>	-	Plate
Plate Thickness:0.300 Inches MaximumPlate Width:0.668 Inches Maximum NutNut Counterbore Depth:0.135 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mountingo,998 Inches Minimum And 0.505 Inches MaximumCenter:0.998 Inches Minimum And 0.505 Inches MaximumCenter:0.998 Inches Minimum And 0.502 Inches MaximumForma Aperture Center Distance Between Mounting0.998 Inches Minimum And 0.502 Inches MaximumForma Rating:0.505 Inches MaximumForma Aperture Center Distance Between Mounting0.998 Inches MaximumForma Rating:0.505 Inches MaximumForma Rating:0.505 Inches MaximumForma Rating:0.505 Inches MaximumForma Portuled:Ninour And 0.602 Inches MaximumThread Series:0.505 Inches MaximumForma Portuled:0.505 Inches MaximumMaterial:0.505 Inches Maximum<	Nut Length:	1.296 Inches Maximum
Plate Width:0.668 Inches MaximumNut Counterbore Depth:0.135 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Conternoitof syle Inches Minimum And 0.505 Inches MaximumCenter:0.998 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mountingof syle Inches Minimum And 0.505 Inches MaximumTemp Rating:0.998 Inches Minimum And 0.505 Inches MaximumTemp Rating:0.998 Inches Minimum And 0.505 Inches MaximumTemp Rating:0.908 Inches Minimum And 0.505 Inches MaximumTemp Rating:0.908 Inches Minimum And 0.505 Inches MaximumThread Series:0.908 Inches Minimum And 0.505 Inches MaximumThread Series:0.908 Inches MaximumThread Series:0.908 Inches MaximumMaterial:0.500 InchesMaterial:0.500 InchesMaterial:0.601 InchesMaterial:0.601 InchesMaterial:0.601 InchesMaterial:0.601 InchesMaterial:0.601 InchesMaterial:<	Nut Height:	0.372 Inches Maximum
Nut Counterbore Depth:0.135 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Holeo.495 Inches Minimum And 0.505 Inches MaximumCenter:0.998 Inches Minimum And 0.505 Inches MaximumCenter Distance Between Mountingo.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:25.0 Deg Fahrenheit NominalThread Series:UnjfFoatures Provided:Foating NutThread Quantity Per Inch:250 Inches Sum All Subject State StateMaterial:Aluminum Ally Washer Or Steel WasherMaterial:Scel NutMaterial:Steel NutMaterial:Steel ShellMaterial:Steel ShellMaterial:Steel ShellMaterial:Mil-se85:class 1.grade 60 Mill Spec Single Material Response SealSurface Treatment:Cadmium Nut	Plate Thickness:	0.030 Inches Maximum
Nut Mounting Provision:Staight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Wold>d>d>sl Si Inches Minimu And 0.505 Inches MaximumCenter:0 sp8 Inches Minimu And 0.002 Inches MaximumCenter To Center Distance Between Mounting0 sp8 Inches Minimu And 1.002 Inches MaximumToteg Length:0 sp8 Inches MaximumToteg Length:0 sp8 Inches MaximumToteg Length:0 sp8 Inches MaximumToteg Length:0 sp8 Inches MaximumMaterial:0 sp8 Inches Maximum And 1.002 Inches MaximumMaterial:0 se0 Sunt Inches MaximumMaterial:0 se0 Sunt Inches MaximumMaterial:0 se0 Sunt Inches Sunt	Plate Width:	0.668 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:225.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Mominal Thread Size:0.250 InchesMaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Steel Synthetic SealMaterial:Steel NutMaterial:Steel ShellMaterial:Steel ShellMaterial:Mils-6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Cadmium NutSurface Treatment:Cadmium Nut	Nut Counterbore Depth:	0.135 Inches Minimum Nut
Distance From Aperture Center To Mounting Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:225.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:8Nominal Thread Size:0.250 InchesMaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Kuber Synthetic SealMaterial:Steel NutMaterial:Steel SultMaterial:Steel SultMaterial:Mils-6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Cadmium Nut	Nut Mounting Provision:	Straight Holes
Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter:0.998 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:25.0 Deg Fahrenheit NominalTemp Rating:25.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Nominal Thread Size:0.250 InchesMaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Rubber Synthetic SealMaterial:Steel NutMaterial:Steel NutMaterial:Steel ShellMaterial:Mil-s-6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Cadmium Nut	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:225.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Nominal Thread Size:0.250 InchesMaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Rubber Synthetic SealMaterial:Steel NutMaterial:Steel ShellMaterial:Material:Material:Mil-s-6855.class 1.grade 60 Mil Spec Single Material Response SealSurface Treatment:Cadmium Nut	Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Thread Series:UnjfFeatures Provided:Foating NutThread Quantity Per Inch:28Nominal Thread Size:0.250 InchesNaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Ruber Synthetic SealMaterial:Steel NutMaterial:Steel NutMaterial:Steel NutMaterial:Steel ShellMaterial:Steel Sclass 1,grade 60 Mil Spec Single Material Response SealMaterial:Andrize Super Schass 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Cadmium NutSurface Treatment:Cadmium Nut	Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Features Provided:Foating NutThread Quantity Per Inch:28Nominal Thread Size:0.250 InchesMaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Rubber Synthetic SealMaterial:Steel NutMaterial:Steel NutMaterial:Steel NutMaterial:Steel ScalMaterial:Mil-s-6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Cadmium Nut	Temp Rating:	225.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch:28Nominal Thread Size:0.250 InchesMaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Rubber Synthetic SealMaterial:Steel NutMaterial:Steel ShellMaterial Document And Classification:Mil-se855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Cadmium NutSurface Treatment:Cadmium Nut	Thread Series:	Unjf
Nominal Thread Size:0.250 InchesMaterial:Aluminum Alloy Washer Or Steel WasherMaterial:Rubber Synthetic SealMaterial:Steel NutMaterial:Steel NutMaterial:Steel ShellMaterial Document And Classification:Mil-s-6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Anodize Washer Or Oxide Film Washer Or Cadmium WasherSurface Treatment:Cadmium Nut	Features Provided:	Floating Nut
Material:Aluminum Alloy Washer Or Steel WasherMaterial:Rubber Synthetic SealMaterial:Steel NutMaterial:Steel ShellMaterial:Steel ShellMaterial:Mil-s6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Anodize Washer Or Oxide Film Washer Or Cadmium WasherSurface Treatment:Cadmium Nut	Thread Quantity Per Inch:	28
Material:Rubber Synthetic SealMaterial:Steel NutMaterial:Steel ShellMaterial Document And Classification:Mil-s-6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Anodize Washer Or Oxide Film Washer Or Cadmium WasherSurface Treatment:Cadmium Nut	Nominal Thread Size:	0.250 Inches
Material:Steel NutMaterial:Steel ShellMaterial Document And Classification:Mil-s-6855,class 1,grade 60 Mil Spec Single Material Response SealSurface Treatment:Anodize Washer Or Oxide Film Washer Or Cadmium WasherSurface Treatment:Cadmium Nut	Material:	Aluminum Alloy Washer Or Steel Washer
Material:Steel ShellMaterial Document And Classification:Mil-s-6855, class 1, grade 60 Mil Spec Single Material Response SealSurface Treatment:Anodize Washer Or Oxide Film Washer Or Cadmium WasherSurface Treatment:Cadmium Nut	Material:	Rubber Synthetic Seal
Material Document And Classification:Mil-s-6855, class 1, grade 60 Mil Spec Single Material Response SealSurface Treatment:Anodize Washer Or Oxide Film Washer Or Cadmium WasherSurface Treatment:Cadmium Nut	Material:	Steel Nut
Surface Treatment: Anodize Washer Or Oxide Film Washer Or Cadmium Washer   Surface Treatment: Cadmium Nut	Material:	Steel Shell
Surface Treatment: Cadmium Nut	Material Document And Classification:	Mil-s-6855, class 1, grade 60 Mil Spec Single Material Response Seal
	Surface Treatment:	Anodize Washer Or Oxide Film Washer Or Cadmium Washer
Surface Treatment: Cadmium Shell	Surface Treatment:	Cadmium Nut
	Surface Treatment:	Cadmium Shell

Surface Treatment Document And Classification:	Mil-a-8625,type 1 Mil Spec 1st Treatment Response Washer Or Mil-c-5541 Mil Spec 2nd Treatment Response Washer Or Qq-p-416 Fed Spec 3rd Treatment Response Washer
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Shell
Specification/standard Data:	80205-nas1473 Professional/industrial Association Standard

## How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1473A4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.