

Description

thread: 5/16-24, self locking, cap, two lug, nut and shell, NAS1473 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1473A5
Minimum Qty (MOQ):	5
NSN:	5310-00-974-6614
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1473A5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.352 Inches Minimum Base
Lubrication:	Dry Film Lubricant
Overall Height:	0.798 Inches Maximum
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.280 Inches Nominal
Nut Height:	0.410 Inches Maximum
Plate Thickness:	0.018 Inches Nominal
Plate Width:	0.762 Inches Maximum
Nut Counterbore Depth:	0.135 Inches Minimum Base
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	-80.0 Deg Fahrenheit Minimum And 250.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Material:	Aluminum Alloy Base
Material:	Rubber Synthetic Seal
Material:	Steel Nut
Material:	Steel Shell
Material Document And Classification:	Mil-r-6855,cl 1 Mil Spec Single Material Response Seal
Surface Treatment:	Anodize Base
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Cadmium Shell And Chromate Shell

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1473A5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.