

P/N NAS1473C08

Military-Fasteners.com

Description

thread: 8-32, self locking, two lug, silver, corrosion resistant, NAS1473 series nut

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1473C08
Minimum Qty (MOQ):	5
NSN:	5310-01-309-7728
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1473C08 Specifications

Locking Feature:Pavailing Torque All Metal DesignOverall Height:0.640 Inches MaximumMounting Hole Diameter:0.098 Inches Minimum And 0.102 Inches MaximumNut Style:PateNut Length:0.989 Inches MaximumNut Length:0.999 Inches MaximumNut Length:0.313 Inches MaximumPlate Thickness:0.30 Inches MaximumPlate Thickness:0.30 Inches MaximumPlate Thickness:0.30 Inches MaximumPlate Thickness:0.30 Inches MaximumDistance Form Aperture Center To Mounting Hole Center:0.399 Inches Minimum And 0.349 Inches MaximumDistance Form Aperture Center To Mounting Hole Center:0.390 Inches MaximumCenter Distance Between Mounting Holes Along0.666 Inches Minimum And 0.690 Inches MaximumThread Series:0.900 Inches MaximumThread Series:0.164 InchesNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 NasherMaterial:Ruber Silicone Class o SealMaterial:Ruber Silicone Class o SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response Sut Of Ams 5525 Assn Std Single Material Response Sut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material Response Nut Of Ams 5525 Assn Std Single Material R	Thread Class:	3b
Overall Height:0.640 Inches MaximumMounting Hole Diameter:0.098 Inches Minimum And 0.102 Inches MaximumNut Style:PlateNut Length:0.989 Inches MaximumNut Height:0.398 Inches MaximumNut Height:0.301 Inches MaximumPlate Thickness:0.030 Inches MaximumPlate Width:0.568 Inches MaximumNut Mounting Provision:Sraight HolesNut Mounting Provision:0.399 Inches Minimum And 0.349 Inches MaximumCenter To Mounting Hole Center:0.399 Inches Minimum And 0.499 Inches MaximumCenter To Center Distance Between Mounting Hole Center:0.399 Inches Minimum And 0.690 Inches MaximumCenter To Schare Distance Between Mounting Hole Center:0.166 Inches Minimum And 0.690 Inches MaximumCenter To Schare Distance Between Mounting Hole Center:0.166 Inches Minimum And 0.690 Inches MaximumTread Quantity Per Inch:32Toread Scrie:UnicMaterial:Inch Alloy 660 NutMaterial:Inch Alloy 660 ShellMaterial:Inch Alloy 660 ShellMaterial:Ans 200 Sass Std Single Material Response ShellMaterial Document And Classification:Ams 525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 523 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 523 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 523 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 523 Assn Std Single Material Response Shell	Thread Direction:	Right-hand
Mounting Hole Diameter:0.098 Inches Minimum And 0.102 Inches MaximumNut Style:PlateNut Length:0.399 Inches MaximumNut Height:0.313 Inches MaximumPlate Thickness:0.303 Inches MaximumPlate Thickness:0.303 Inches MaximumNut Mounting Provision:0.568 Inches MaximumMut Mounting Provision:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Batween Mounting Hole Arrange0.666 Inches Minimum And 0.590 Inches MaximumTemp Rating:0.666 Inches Minimum And 0.690 Inches MaximumThread Series:UnicMounting Hole Arrange0.666 Inches Minimum And 0.690 Inches MaximumMonting Hole Arrange0.666 Inches Minimum And 0.690 Inches MaximumThread Series:UnicMonting Hole Arrange0.666 InchesMaterial:Inch Allo 660 NutMaterial:Inch Allo 660 NutMaterial:Inch Allo 660 MasherMaterial:Rubber Sillcone Class O SealMaterial:Non Allo 660 MasherMaterial Document And Classification:Ams 5325 Assn Std Single Material Response ShellMaterial Document And Classification:Sms 5325 Assn Std Single Material Response ShellMaterial Document And Classification:Mms 5325 Assn Std Single Material Response ShellMaterial Document And Classification:Mms 5325 Assn Std Single Material Response Nut or Ams 5525 Assn Std Single Material Response Nut or Ams 5525 Assn Std Single Material Response Nut or Ams 5525 Assn Std Single Material Respon	Locking Feature:	Prevailing Torque All Metal Design
Nut Style:PiateNut Length:0.989 Inches MaximumNut Height:0.313 Inches MaximumPlate Thickness:0.300 Inches MaximumPlate Thickness:0.568 Inches MaximumPlate Width:0.568 Inches MaximumNut Mounting Provision:Stralight HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumDistance From Aperture Center To Mounting Hole Arrange0.368 Inches Minimum And 0.690 Inches MaximumCenter To Center Distance Between Mounting Holes Along0.668 Inches Minimum And 0.690 Inches MaximumTemp Rating:0.668 Inches Minimum And 0.690 Inches MaximumTempating:0.668 Inches Minimum And 0.690 Inches MaximumThread Series:UnjcNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Nut Silcone Class of Saling Material Response SealMaterial Document And Classification:Mis 5525 Assn Std Single Material Response SealMaterial Document And Classification:Smis 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material ResponseMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Stans Std Single Material ResponseMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Stans Std Single Material ResponseMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Stans Std Single Material Response Stans Std Single Material Response Stans Std Sin	Overall Height:	0.640 Inches Maximum
Nut Length:0.989 Inches MaximumNut Height:0.331 Inches MaximumPlate Mich0.303 Inches MaximumPlate Mich0.303 Inches MaximumPlate Width:0.568 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter Distance Between Mounting Holes Along0.666 Inches Minimum And 0.690 Inches MaximumCenter Stance Between Mounting Holes Along0.686 Inches Minimum And 0.690 Inches MaximumTemp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjcTomal Quantity Per Inch:32Material:Iron Alloy 660 NutMaterial:Iron Alloy 660 NutMaterial:Rub Silicone Class O SealMaterial:Num Silicone Class O SealMaterial:Num Silicone Class O SealMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5572 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5572 Assn Std Single Material Response ShellMaterial Document And Classification:Num Si732 Assn Std Single Material Response ShellMaterial Document And Classification:Num Si732 Assn Std Single Material Response ShellMaterial Document And Classification:Num Si732 Assn Std Single Material Response ShellMaterial Document And Classification:Num Si732 Assn Std Single Material Response ShellMaterial Do	Mounting Hole Diameter:	0.098 Inches Minimum And 0.102 Inches Maximum
Nut Height:0.313 Inches MaximumPlate Thickness:0.030 Inches MaximumPlate Width:0.668 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:6.686 Inches Minimum And 0.690 Inches MaximumTemp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjcThread Quantity Per Inch:2Material:Iron Alloy 660 NutMaterial:Iron Alloy 660 NutMaterial:Non Alloy 660 ShellMaterial:Ans 3504 Assn 5td Single Material Response ShellMaterial:Ans 5525 Assn 5td Single Material Response ShellMaterial Document And Classification:Ans 5732 Assn 5td Single Material Response Subter Or Ams 5525 Assn 5td Single Material Response ShellMaterial Document And Classification:Nos 5732 Assn 5td Single Material Response ShellMaterial And Location:Nut SilverPrecious Material And Location:Nut Silver	Nut Style:	Plate
Plate Thickness:0.030 inches MaximumPlate Width:0.568 inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:0.339 inches Minimum And 0.349 inches MaximumDistance From Aperture Center To Mounting Hole Center:0.339 inches Minimum And 0.690 inches MaximumCenter To Center Distance Between Mounting Hole Stalong0.686 inches Minimum And 0.690 inches MaximumTemp Rating:0.500 Deg Fahrenheit MaximumThread Quantity Per Inch:32Nominal Thread Size:0.164 inchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Roule Glass O ScalMaterial:Roule Signie Material Response ScalMaterial:Material Stalongen ScalMaterial Document And Classification:Ams 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response ShellMater	Nut Length:	0.989 Inches Maximum
Plate Width:0.568 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Alongo.666 Inches Minimum And 0.690 Inches MaximumCenter To Center Distance Between Mounting Holes Alongo.666 Inches Minimum And 0.690 Inches MaximumTherad Series:UnjcThread Quantity Per Inch:32Nomian Thread Size:Inch Alloy 660 NutMaterial:Inch Alloy 660 NutMaterial:Nut Sizi Saxon Std Single Material Response SealMaterial:Material Response SealMaterial Document And Classification:Mas 573 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Nut Or Arms 5525 Assn Std Single Material Response Std Single Material Response Nut	Nut Height:	0.313 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.686 Inches Minimum And 0.690 Inches MaximumTemp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnicThread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMaterial:Iron Allog 660 NulMaterial:Iron Allog 660 ShellMaterial:Iron Allog 660 ShellMaterial:Iron Allog 660 ShellMaterial:Muber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5732 Assn Std Single Material Response SulMaterial Document And Classification:Sins 732 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response SulMaterial Document And Classification:Sins 732 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 5525 Assn Std Single Material Response Wather Or Ams 552	Plate Thickness:	0.030 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.686 Inches Minimum And 0.690 Inches MaximumTemp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjcThread Series:0.164 InchesMounting Hole Zenter:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Arms 3304 Assn Std Single Material Response SealMaterial Document And Classification:Arms 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Arms 5732 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Sut Or Ams 5525 Assn Std Single Material Response Material Response Sut Or Ams 5525 Assn Std Single Material Response Material Response Material Response Material Response Sut Or Ams 5525 Assn Std Single Material Response Material Response Sut Or Ams 5525 Assn Std Single Material Response Mate	Plate Width:	0.568 Inches Maximum
Distance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.686 Inches Minimum And 0.690 Inches MaximumTemp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnicThread Quartity Per Inch:32Nominal Thread Size:Infol 4 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 WasherMaterial:Rubber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Nut SilverMaterial Document And Classification:Nut Silver	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length:0.686 Inches Minimum And 0.690 Inches MaximumTemp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjcThread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Rubber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Material Response Nut Or Ams 5525 Assn Std Single Material Response Material Response Material Response Nut Or Ams 5525 Assn Std Single Material Response Material Response Nut Or Ams 5525 Assn Std Single Material Response Material Response Material Response Material Res	Mounting Hole Arrangement Style:	2 Holes
Length:0.886 increas Minimum And 0.890 increas MaximumTemp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjcThread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Nominal Thread Size:Material:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Nominal Size:Material:Nominal Size:Material:Nom Alloy 660 ShellMaterial:Nom Alloy 660 ShellMaterial Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Ma	Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Thread Series:UnjcThread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 NusherMaterial:Nubler Silicone Class Q SealMaterial Document And Classification:Mas 5525 Assn Std Single Material Response SealMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Suble Material Response SubleMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Suble Material ResponseMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Suble Material ResponseMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material ResponsePrecious Material And Location:Nut SilverPrecious Material:Silver	Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Thread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 WasherMaterial:Rubber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Sing	Temp Rating:	450.0 Deg Fahrenheit Maximum
Nominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 WasherMaterial:Ruber Silicone Class Q SealMaterial Document And Classification:Ams 304 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5752 Assn Std Single Material Response ShellMaterial Document And Classification:Mas 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material ResponsePrecious Material And Location:Nut SilverPrecious Material:Silver	Thread Series:	Unjc
Material:iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial:Iron Alloy 660 WasherMaterial:Rubber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material ResponsePrecious Material And Location:Nut SilverPrecious Material And Location:Silver	Thread Quantity Per Inch:	32
Material:Iron Alloy 660 ShellMaterial:Iron Alloy 660 WasherMaterial:Rubber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material ResponseMaterial Document And Classification:Mis 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material ResponsePrecious Material And Location:Nut SilverPrecious Material:Silver	Nominal Thread Size:	0.164 Inches
Material:Iron Alloy 660 WasherMaterial:Rubber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material Response WasherPrecious Material And Location:Nut SilverPrecious Material:Silver	Material:	Iron Alloy 660 Nut
Material:Rubber Silicone Class Q SealMaterial Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material ResponsePrecious Material And Location:Nut SilverPrecious Material:Silver	Material:	Iron Alloy 660 Shell
Material Document And Classification:Ams 3304 Assn Std Single Material Response SealMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material ResponsePrecious Material And Location:Nut SilverPrecious Material:Silver	Material:	Iron Alloy 660 Washer
Material Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material ResponsePrecious Material And Location:Nut SilverPrecious Material:Silver	Material:	Rubber Silicone Class Q Seal
Material Document And Classification:Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material Response WasherPrecious Material And Location:Nut SilverPrecious Material:Silver	Material Document And Classification:	Ams 3304 Assn Std Single Material Response Seal
Material Document And Classification:Ams 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material Response WasherPrecious Material And Location:Nut SilverPrecious Material:Silver	Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell
Material Document And Classification: Washer Precious Material And Location: Nut Silver Precious Material: Silver	Material Document And Classification:	Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut
Precious Material: Silver	Material Document And Classification:	
	Precious Material And Location:	Nut Silver
Surface Treatment: Silver Nut	Precious Material:	Silver
	Surface Treatment:	Silver Nut

Surface Treatment:	Passivate Shell
Surface Treatment:	Passivate Washer
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shell
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Washer
Specification/standard Data:	80205-nas1473 Professional/industrial Association Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+nutplates/NAS1473C08</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.