

Description

thread: 8-32, self locking, two lug, silver, corrosion resistant, NAS1473 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS1473C08 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-309-7728 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1473C08 Specifications

| | |
|-----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Overall Height: | 0.640 Inches Maximum |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.102 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.989 Inches Maximum |
| Nut Height: | 0.313 Inches Maximum |
| Plate Thickness: | 0.030 Inches Maximum |
| Plate Width: | 0.568 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.339 Inches Minimum And 0.349 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.686 Inches Minimum And 0.690 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Material: | Iron Alloy 660 Nut |
| Material: | Iron Alloy 660 Shell |
| Material: | Iron Alloy 660 Washer |
| Material: | Rubber Silicone Class Q Seal |
| Material Document And Classification: | Ams 3304 Assn Std Single Material Response Seal |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Shell |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Nut Or Ams 5525 Assn Std Single Material Response Nut |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Washer Or Ams 5525 Assn Std Single Material Response Washer |
| Precious Material And Location: | Nut Silver |
| Precious Material: | Silver |
| Surface Treatment: | Silver Nut |

| | |
|-------------------------------------------------------|------------------------------------------------------------|
| Surface Treatment: | Passivate Shell |
| Surface Treatment: | Passivate Washer |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Nut |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Shell |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Washer |
| Specification/standard Data: | 80205-nas1473 Professional/industrial Association Standard |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1473C08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.