

## **P/N NAS1473C4**

## **Description**

Thread: 1/4-28, Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS1473C4

Minimum Qty (MOQ): 5

NSN: 5310-00-045-5636

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS1473C4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.289 Inches Minimum Nut
Overall Height:	0.755 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.296 Inches Maximum
Nut Height:	0.372 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.668 Inches Maximum
Nut Counterbore Depth:	0.135 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.500 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	1.000 Inches Nominal
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Base
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Shell
Material Document And Classification:	Ams 3304 Assn Std Single Material Response Seal
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Base Or Ams 5732 Assn Std Single Material Response Base
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell Or Ams 5732 Assn Std Single Material Response Shell
Surface Treatment:	Silver Nut

Surface Treatment:	Passivate Base
Surface Treatment:	Passivate Shell
Specification/standard Data:	80205-nas1474 Professional/industrial Association Standard

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS1473C4">https://military-fasteners.com/nuts/locknuts/NAS1473C4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/NAS1473C4">https://military-fasteners.com/nuts/locknuts/NAS1473C4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/NAS1473C4">https://military-fasteners.com/nuts/locknuts/NAS1473C4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/NAS1473C4">https://military-fasteners.com/nuts/locknuts/NAS1473C4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/NAS1473C4">https://military-fasteners.com/nuts/locknuts/NAS1473C4</a> and selecting the property of the property