

Description

Thread Size: 19/64", Nut Length: 1-9/32", Nut Height: 13/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1473C5
Minimum Qty (MOQ):	5
NSN:	5310-00-781-7094
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1473C5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.351 Inches Minimum Nut
Overall Height:	0.823 Inches Maximum
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.296 Inches Maximum
Nut Height:	0.410 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.762 Inches Maximum
Nut Counterbore Depth:	0.135 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	-65.0 Deg Fahrenheit Minimum And 450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Shell
Material:	Iron Alloy 660 Washer
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Nut Or Ams 5735 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Washer Or Ams 5735 Assn Std Single Material Response Washer
Material Document And Classification:	Mil-r-6825,class 1,grade 60 Mil Spec Single Material Response Seal
Surface Treatment:	Passivate Nut

Surface Treatment:	Passivate Shell
Surface Treatment:	Passivate Washer
Specification/standard Data:	80205-nas1473 Professional/industrial Association Standard

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1473C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.