

Description

Thread Size: 3/16", Nut Length: 1", Nut Height: 5/16", two lug, NAS1473 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1473F3
Minimum Qty (MOQ):	5
NSN:	5310-01-267-2877
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1473F3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Overall Height:	0.640 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.989 Inches Maximum
Nut Height:	0.313 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.568 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	350.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Rubber Fluorosilicone Class Fq Seal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Mil-r-25988 Mil Spec Single Material Response Seal
Surface Treatment:	Passivate Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut
Specification/standard Data:	80205-nas1473 Professional/Industrial Association Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1473F3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.