

Description

Thread Size: 1/4", Nut Length: 1-9/32", Nut Height: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1473F4
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-326-4928
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1473F4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Overall Height:	0.755 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.296 Inches Maximum
Nut Height:	0.372 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.668 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	350.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material:	Rubber Fluorosilicone Class Fq Seal
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall
Material Document And Classification:	Mil-r-25988 Mil Spec Single Material Response Seal
Surface Treatment:	Passivate Nut
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Nut
Specification/standard Data:	80205-nas1473 Professional/Industrial Association Standard

How to Order

Order this cap plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1473F4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.