

P/N NAS1473F4

Description

Thread Size: 1/4", Nut Length: 1-9/32", Nut Height: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1473F4

Minimum Qty (MOQ): 5 EA

NSN: 5310-01-326-4928

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1473F4 Specifications

Thread Direction: Locking Feature: Prevailing Torque All Metal Design Dry Film Lubricant Overall Height: O.755 Inches Maximum Mounting Hole Diameter: O.998 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: O.372 Inches Maximum Nut Height: O.372 Inches Maximum Plate Thickness: O.030 Inches Maximum Plate Width: O.668 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: O.495 Inches Minimum And 0.505 Inches Maximum Distance From Aperture Center To Mounting Hole Center: O.495 Inches Minimum And 0.505 Inches Maximum
Lubrication:Dry Film LubricantOverall Height:0.755 Inches MaximumMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:1.296 Inches MaximumNut Height:0.372 Inches MaximumPlate Thickness:0.030 Inches MaximumPlate Width:0.668 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 Holes
Overall Height: O.755 Inches Maximum Mounting Hole Diameter: O.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: O.372 Inches Maximum Nut Height: O.372 Inches Maximum Plate Thickness: O.030 Inches Maximum Plate Width: O.668 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes
Mounting Hole Diameter: Nut Style: Nut Length: Nut Height: Nut Height: O.098 Inches Minimum And 0.103 Inches Maximum 1.296 Inches Maximum O.372 Inches Maximum Plate Thickness: O.030 Inches Maximum Plate Width: O.668 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes
Nut Style: Nut Length: Nut Height: Nut Height: O.372 Inches Maximum Plate Thickness: O.030 Inches Maximum Plate Width: O.668 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes
Nut Length:1.296 Inches MaximumNut Height:0.372 Inches MaximumPlate Thickness:0.030 Inches MaximumPlate Width:0.668 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 Holes
Nut Height: Plate Thickness: 0.372 Inches Maximum 0.372 Inches Maximum 0.030 Inches Maximum 0.668 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes
Plate Thickness: 0.030 Inches Maximum 0.668 Inches Maximum Nut Mounting Provision: Straight Holes 4 Holes
Plate Width: Nut Mounting Provision: Mounting Hole Arrangement Style: 2 Holes
Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes
Mounting Hole Arrangement Style: 2 Holes
Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum
Distance From Aperture Center to Flounding Hole Center.
Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating: 350.0 Deg Fahrenheit Nominal
Thread Series: Unjf
Features Provided: Floating Nut
Thread Quantity Per Inch: 28
Nominal Thread Size: 0.250 Inches
Material: Iron Alloy 660 Overall
Material: Rubber Fluorosilicone Class Fq Seal
Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall
Material Document And Classification: Mil-r-25988 Mil Spec Single Material Response Seal
Surface Treatment: Passivate Nut
Surface Treatment Document And Classification: Mil-s-5002 Mil Spec Single Treatment Response Nut
Specification/standard Data: 80205-nas1473 Professional/industrial Association Standard

How to Order Order this cap plate - two lug locknut from our inventory online by visiting https://military-fasteners.com/nuts/locknuts/NAS1473F4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.