



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1474A04**

## Description

thread: 4-40, self-locking capped nutplate, reduced rivet spacing, two lug steel nut and shell

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1474A04                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5310-00-143-6338                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N NAS1474A04 Specifications

|  |  |
|--|--|
| Thread Class:  | 3b   |
| Thread Direction:  | Right-hand   |
| Locking Feature:   | Prevailing Torque All Metal Design                                 |
| Counterbore Diameter:  | 0.142 Inches Minimum Nut   |
| Lubrication:   | Dry Film Lubricant   |
| Overall Height:  | 0.405 Inches Maximum   |
| Mounting Hole Diameter:  | 0.098 Inches Nominal   |
| Nut Style:   | Plate  |
| Nut Length:  | 0.840 Inches Maximum   |
| Nut Height:  | 0.204 Inches Maximum   |
| Plate Thickness:   | 0.030 Inches Maximum   |
| Plate Width:   | 0.443 Inches Maximum   |
| Nut Counterbore Depth:   | 0.070 Inches Minimum Nut   |
| Nut Mounting Provision:  | Straight Holes   |
| Mounting Hole Arrangement Style:                               | 2 Holes  |
| Distance From Aperture Center To Mounting Hole Center:         | 0.290 Inches Minimum And 0.300 Inches Maximum                      |
| Center To Center Distance Between Mounting Holes Along Length: | 0.588 Inches Minimum And 0.592 Inches Maximum                      |
| Temp Rating:   | -65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum      |
| Thread Series:   | Unjc   |
| Features Provided:   | Floating Nut   |
| Thread Quantity Per Inch:                                      | 40   |
| Nominal Thread Size:   | 0.112 Inches   |
| Material:  | Rubber Synthetic Seal  |
| Material:  | Steel Nut  |
| Material:  | Steel Shell  |
| Material Document And Classification:                          | Mil-s-6855,class 1,grade 60 Mil Spec Single Material Response Seal |
| Surface Treatment:   | Cadmium Nut  |
| Surface Treatment:   | Cadmium Shell  |
| Surface Treatment Document And Classification:                 | Qq-p-416 Fed Spec Single Treatment Response Nut                    |
| Surface Treatment Document And Classification:                 | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Shell   |
| Specification/standard Data:                                   | 80205-nas1474 Professional/industrial Association Standard         |

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1474A04](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A04) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.