

P/N NAS1474A06

Description

thread: 6-32, self locking, capped, reduced rivet spacing, two lug, steel nut and shell, NAS1474 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1474A06

Minimum Qty (MOQ): 5

NSN: 5310-00-136-7794

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













^{*} See page 2 for technical characteristics

P/N NAS1474A06 Specifications

Thread Class	2h
Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.173 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Overall Height:	0.405 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Nominal
Nut Style:	Plate
Nut Length:	0.840 Inches Maximum
Nut Height:	0.221 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.443 Inches Maximum
Nut Counterbore Depth:	0.070 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.290 Inches Minimum And 0.300 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.588 Inches Minimum And 0.592 Inches Maximum
Temp Rating:	-65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Rubber Synthetic Seal
Material:	Steel Nut
Material:	Steel Shell
Material:	Steel Washer Or Aluminum Washer
Material Document And Classification:	Mil-r-6855, Class 1, Grade 60 Mil Spec Single Material Response Seal
Surface Treatment:	Cadmium Nut
Surface Treatment:	Cadmium Shell
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Shell

How to Order Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the part of t