

P/N NAS1474A06

Description

thread: 6-32, self locking, capped, reduced rivet spacing, two lug, steel nut and shell, NAS1474 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1474A06

Minimum Qty (MOQ): 5

NSN: 5310-00-136-7794

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













^{*} See page 2 for technical characteristics

P/N NAS1474A06 Specifications

| Thread Class | 2h |
|--|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Counterbore Diameter: | 0.173 Inches Minimum Nut |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.405 Inches Maximum |
| Mounting Hole Diameter: | 0.098 Inches Nominal |
| Nut Style: | Plate |
| Nut Length: | 0.840 Inches Maximum |
| Nut Height: | 0.221 Inches Maximum |
| Plate Thickness: | 0.030 Inches Maximum |
| Plate Width: | 0.443 Inches Maximum |
| Nut Counterbore Depth: | 0.070 Inches Minimum Nut |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.290 Inches Minimum And 0.300 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.588 Inches Minimum And 0.592 Inches Maximum |
| Temp Rating: | -65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjc |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Material: | Rubber Synthetic Seal |
| Material: | Steel Nut |
| Material: | Steel Shell |
| Material: | Steel Washer Or Aluminum Washer |
| Material Document And Classification: | Mil-r-6855, Class 1, Grade 60 Mil Spec Single Material Response Seal |
| Surface Treatment: | Cadmium Nut |
| Surface Treatment: | Cadmium Shell |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Nut |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Shell |
| | |

How to Order Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06 and selecting the part of t