

**Description**

thread: 6-32, self locking, capped, reduced rivet spacing, two lug, steel nut and shell, NAS1474 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1474A06
Minimum Qty (MOQ):	5
NSN:	5310-00-136-7794
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1474A06 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.173 Inches Minimum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Overall Height:</b>	0.405 Inches Maximum
<b>Mounting Hole Diameter:</b>	0.098 Inches Nominal
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.840 Inches Maximum
<b>Nut Height:</b>	0.221 Inches Maximum
<b>Plate Thickness:</b>	0.030 Inches Maximum
<b>Plate Width:</b>	0.443 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.070 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.290 Inches Minimum And 0.300 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.588 Inches Minimum And 0.592 Inches Maximum
<b>Temp Rating:</b>	-65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unjc
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Material:</b>	Rubber Synthetic Seal
<b>Material:</b>	Steel Nut
<b>Material:</b>	Steel Shell
<b>Material:</b>	Steel Washer Or Aluminum Washer
<b>Material Document And Classification:</b>	Mil-r-6855, Class 1, Grade 60 Mil Spec Single Material Response Seal
<b>Surface Treatment:</b>	Cadmium Nut
<b>Surface Treatment:</b>	Cadmium Shell
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Shell

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1474A06](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A06) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.