

Description

thread: 10-32, self locking, capped, reduced rivet spacing, two lug, steel nut and shell, NAS1474 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

10SD25A307B25

SKU / Model:	NAS1474A3
Minimum Qty (MOQ):	10
NSN:	5310-00-905-5473
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1474A3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Overall Height:	0.405 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Nominal
Nut Style:	Plate
Nut Length:	0.840 Inches Maximum
Nut Height:	0.268 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.443 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.290 Inches Minimum And 0.300 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.588 Inches Minimum And 0.592 Inches Maximum
Temp Rating:	225.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.