

**Description**

thread: 1/4-28, self-locking, capped, reduced rivet spacing, two lug, steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1474A4
Minimum Qty (MOQ):	10
NSN:	5310-00-994-7209
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N NAS1474A4 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.280 Inches Minimum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Overall Height:</b>	0.560 Inches Maximum
<b>Mounting Hole Diameter:</b>	0.098 Inches Nominal
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	1.000 Inches Maximum
<b>Nut Height:</b>	0.350 Inches Maximum
<b>Plate Thickness:</b>	0.030 Inches Maximum
<b>Plate Width:</b>	0.635 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.105 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.371 Inches Minimum And 0.381 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.750 Inches Minimum And 0.754 Inches Maximum
<b>Temp Rating:</b>	-65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	60.0 Shore Durometer A Nominal
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Aluminum Alloy Washer Or Steel Washer
<b>Material:</b>	Rubber Synthetic Seal
<b>Material:</b>	Steel Nut
<b>Material:</b>	Steel Shell
<b>Material Document And Classification:</b>	Mil-r-6855,class 1,grade 60 Mil Spec Single Material Response Seal
<b>Surface Treatment:</b>	Anodize Washer Or Cadmium Washer
<b>Surface Treatment:</b>	Cadmium Nut

<b>Surface Treatment:</b>	Cadmium Shell
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 1 Mil Spec 1st Treatment Response Washer Or Qq-p-416 Fed Spec 2nd Treatment Response Washer
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 1,class 3 Fed Spec Single Treatment Response Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 1,class 3 Fed Spec Single Treatment Response Shell
<b>Specification/standard Data:</b>	80205-nas1474 Professional/industrial Association Standard

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1474A4](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474A4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.