



★ FASTENERS

Military-Fasteners.com

P/N NAS1474C04

Description

Thread Size: 7/64", Nut Length: 53/64", Nut Height: 13/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1474C04 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5310-00-075-4033 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1474C04 Specifications

| | |
|--|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Counterbore Diameter: | 0.142 Inches Minimum Nut |
| Overall Height: | 0.405 Inches Maximum |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.840 Inches Maximum |
| Nut Height: | 0.204 Inches Maximum |
| Plate Thickness: | 0.030 Inches Maximum |
| Plate Width: | 0.443 Inches Maximum |
| Nut Counterbore Depth: | 0.070 Inches Minimum Nut |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.295 Inches Nominal |
| Center To Center Distance Between Mounting Holes Along Length: | 0.590 Inches Nominal |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjc |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 40 |
| Hardness Rating: | 70.0 Shore Durometer A Nominal |
| Nominal Thread Size: | 0.112 Inches |
| Material: | Iron Alloy 660 Nut |
| Material: | Iron Alloy 660 Shell |
| Material Document And Classification: | Ams 3304 Assn Std Single Material Response Seal |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Shell |
| Precious Material And Location: | Nut External Surfaces Silver |
| Surface Treatment: | Silver Nut |
| Surface Treatment: | Passivate Shell |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Nut |

| | |
|---|--|
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Shell |
| Specification/standard Data: | 80205-nas1474 Professional/industrial Association Standard |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1474C04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.