

**Description**

Thread Size: 1/8", Nut Length: 53/64", Nut Height: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1474C06
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-914-9119
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

# P/N NAS1474C06 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.173 Inches Minimum Nut
<b>Overall Height:</b>	0.405 Inches Maximum
<b>Mounting Hole Diameter:</b>	0.098 Inches Nominal
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.840 Inches Maximum
<b>Nut Height:</b>	0.221 Inches Maximum
<b>Plate Thickness:</b>	0.030 Inches Maximum
<b>Plate Width:</b>	0.443 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.070 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.290 Inches Minimum And 0.300 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.588 Inches Minimum And 0.592 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Material:</b>	Iron Alloy 660 Nut
<b>Material:</b>	Iron Alloy 660 Shell
<b>Material Document And Classification:</b>	Ams 3304 Assn Std Single Material Response Seal
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Shell
<b>Material Document And Classification:</b>	Ams 5732 Assn Std Single Material Response Nut
<b>Precious Material And Location:</b>	Nut Silver
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Nut
<b>Surface Treatment:</b>	Passivate Shell
<b>Surface Treatment Document And Classification:</b>	Ams 2410 Assn Std Single Treatment Response Nut

<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Shell
<b>Specification/standard Data:</b>	80205-nas1474 Professional/industrial Association Standard

## How to Order

Order this cap plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1474C06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.