

**Description**

thread: 10-32, self-locking, capped, reduced rivet spacing, two lug, corrosion resistant


\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[10SX86A307B25](#)

SKU / Model:	NAS1474C3
Minimum Qty (MOQ):	5
NSN:	5310-00-916-4572
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N NAS1474C3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.220 Inches Minimum Nut
Overall Height:	0.405 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Nominal
Nut Style:	Plate
Nut Length:	0.840 Inches Maximum
Nut Height:	0.268 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.443 Inches Maximum
Nut Counterbore Depth:	0.070 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.290 Inches Minimum And 0.300 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.588 Inches Minimum And 0.592 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Shell
Material Document And Classification:	Ams 3304 Assn Std Single Material Response Seal
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Nut
Precious Material And Location:	Nut Silver
Precious Material:	Silver
Surface Treatment:	Silver Nut
Surface Treatment:	Passivate Shell
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Nut

<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Shell
<b>Specification/standard Data:</b>	80205-nas1474 Professional/industrial Association Standard

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1474C3](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474C3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.